

131200120000

Electronic Relay and Actuator: Multi and Single Function




Technical description: Electronic Relays, Call & Reset relay, 35 mm rail (EN 60715) mount, - 17.5 mm wide, 1 pole CO (SPDT) + 1 NO (SPST-NO), 8 A, AC/DC supply version, nominal voltage 12 V, operating from 0.8 to 1.1 V (AC)/(DC), rated power 3 VA (AC) / 2.5 W (DC), AgCdO, Contact circuit: CO + NO, ambient temperature from -10 to +60 °C

Commercial description: Bistable call relay with reset command, 1 CO + 1 NO. Bistable operation with reset command particularly suitable for applications in the tertiary sector: public bathrooms, hospitals, hotels. Mounting on 35 mm rail. Width 17.5 mm

[BROWSE PRODUCT PAGE](#)

Technical Features:

Contact configuration:	1 CO (SPDT) + 1 NO (SPST-NO)
Dimensions:	17.5x84x56.5 mm
Nominal voltage:	12 V
Rated contact voltage:	250 V AC
Rated current (contacts):	8 A
Supply:	AC/DC supply version
Type of installation:	Call & Reset relay, 35 mm rail (EN 60715) mount, 17.5 mm wide
Certifications and quality approvals (according to type):	

Need more information?

[Contact our sales](#) [Find a dealer](#)