

223200244320

Modular contactor








Technical description: Modular contactor, 25 A, 2 pole, NO, 25 A, AgSnO₂, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 9.6 V (AC)/(DC), must drop-out voltage 2.4 V (AC)/(DC), option: Mechanical indicator + LED, ambient temperature from -25 to +50 °C

Commercial description: Modular contactor 25 A, 2 contacts, 17.5mm width, NO contact gap ≥ 3 mm, double break. Suitable for railway applications; plastic materials compliant with fire and smoke regulations (EN 45545-2 + A1: 2016)

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-25...50 °C
Contact configuration:	2 pole, NO
Dimensions:	17.5x84x56.5 mm
Electrical life:	30000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage:	24 V
Operating range ac:	19.2...26.4 V
Operating range dc:	19.2...26.4 V
Rated current contact:	25 A
Rated voltage contact:	250 V AC
Supply version:	AC/DC
Certifications and quality approvals (according to code):	    

Need more information?

[Contact our sales](#) [Find a dealer](#)