

# 223202304320

## Modular contactor








**Technical description:** Modular contactor, 25 A, 2 pole, NO, 25 A, AgSnO<sub>2</sub>, AC/DC coil, 230 V, operating from 184 to 264 V (AC) e da 176 to 242 V (DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 92 V (AC)/(DC), must drop-out voltage 23 V (AC)/(DC), option: Mechanical indicator + LED, ambient temperature from -25 to +50 °C

**Commercial description:** Modular contactor 25 A, 2 contacts, 17.5mm width, NO contact gap  $\geq 3$  mm, double break. Suitable for railway applications; plastic materials compliant with fire and smoke regulations (EN 45545-2 + A1: 2016)

[BROWSE PRODUCT PAGE](#)

### Technical Features:

Ambient temperature range:	-25...50 °C
Contact configuration:	2 pole, NO
Dimensions:	17.5x84x56.5 mm
Electrical life:	30000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage:	230 V
Operating range ac:	184...264 V
Operating range dc:	176...242 V
Rated current contact:	25 A
Rated voltage contact:	250 V AC
Supply version:	AC/DC
Certifications and quality approvals (according to code):	    

**Need more information?**

[Contact our sales](#) [Find a dealer](#)