

# 223400244340

## Modular contactor




**Technical description:** Modular contactor, 25 A, 4 pole, NO, 25 A, AgSnO<sub>2</sub>, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 9.6 V (AC)/(DC), must drop-out voltage 2.4 V (AC)/(DC), option: Auto-On-Off selector + mechanical indicator + LED, ambient temperature from -25 to +50 °C

**Commercial description:** Modular contactor 25 A - 4 contacts, 35mm width and a NO contact gap  $\geq 3$  mm, double break. Type 22.34 complies with EN 61095: 2009

[BROWSE PRODUCT PAGE](#)

### Technical Features:

<b>Ambient temperature range:</b>	-25...50 °C
<b>Contact configuration:</b>	4 pole, NO
<b>Dimensions:</b>	35x84x56.5 mm
<b>Electrical life:</b>	30000 cycles
<b>Insulation coil/contacts:</b>	6 kV
<b>Nominal voltage:</b>	24 V
<b>Operating range ac:</b>	19.2...26.4 V
<b>Operating range dc:</b>	19.2...26.4 V
<b>Rated current contact:</b>	25 A
<b>Rated voltage contact:</b>	250 V AC
<b>Supply version:</b>	AC/DC
<b>Certifications and quality approvals (according to code):</b>	

**Need more information?**

[Contact our sales](#) [Find a dealer](#)