

223402304320

Modular contactor








Technical description: Modular contactor, 25 A, 4 pole, NO, 25 A, AgSnO₂, AC/DC coil, 230 V, operating from 184 to 264 V (AC) e da 176 to 242 V (DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 92 V (AC)/(DC), must drop-out voltage 23 V (AC)/(DC), option: Mechanical indicator + LED, ambient temperature from -25 to +50 °C

Commercial description: Modular contactor 25 A - 4 contacts, 35mm width and a NO contact gap ≥ 3 mm, double break. Type 22.34 complies with EN 61095: 2009

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-25...50 °C
Contact configuration:	4 pole, NO
Dimensions:	35x84x56.5 mm
Electrical life:	30000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage:	230 V
Operating range ac:	184...264 V
Operating range dc:	176...242 V
Rated current contact:	25 A
Rated voltage contact:	250 V AC
Supply version:	AC/DC

Certifications and quality approvals (according to code): EAC   CE  RINA  UL US  UK CA

Need more information?

[Contact our sales](#) [Find a dealer](#)