

PRODUCT-DETAILS

## DDA204 AC-63/0.3 DDA204 AC-63/0.3 Residual Current Device Block



General Information	
Extended Product Type	DDA204 AC-63/0.3
Product ID	2CSB204001R3630
EAN	8012542794707
Catalog Description	DDA204 AC-63/0.3 Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P.  It assures protection against the effects of sinusoidal alternating earth fault currents, protection, against indirects contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.

Technical		
Standards	IEC/EN 61009 Ann. G	
Type of Residual Current	AC type	
Rated Voltage (U <sub>r</sub> )	230/400 V	
Rated Operational Voltage	230/400 V	
Rated Insulation Voltage $(U_i)$	500 V	
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV	
Rated Current (I <sub>n</sub> )	63 A	
Rated Residual Current	300 mA	

DDA204 AC-63/0.3

Leakage Current Type	AC
Rated Frequency (f)	50 60 Hz
Power Loss	7.6 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	4
Operating Characteristic	Instantaneous
Options Provided	-
Connecting Capacity	Rigid 25 25 mm² Flexible 25 25 mm²
Environmental	
Ambient Temperature	-2555 °C
Ambient Air Temperature	Operation -2555 °C
Degree of Protection	IP2X
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 51505 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5614
REACH Declaration	9AKK108467A9482
Environmental Information	Refer to RoHS
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Technical UL/CSA	
Short-Circuit Current	0.3 0.3 A
Rating (SCCR)	
Dimensions	
Product Net Width	140 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.311 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	370 g
E-Number (Finland)	3259824

Declaration of Conformity 9AKK106713A5614

- CE

## Installation Instructions and Manuals 9AKK108467A7091

## Popular Downloads Data Sheet, Technical 9AKK107991A8329 Information

Classifications		
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module	
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
CN8	85363030	
eClass	V11.0 : 27142210	
Object Classification Code	F	

## Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Modular DIN Rail Products} \rightarrow \text{Residual Current Devices RCDs} \rightarrow \text{Residual Current Devices RCD Blocks}$ 





