

PRODUCT-DETAILS

## DDA204 A-40/0.03 DDA204 A-40/0.03 Residual Current Device Block



General Information	
Extended Product Type	DDA204 A-40/0.03
Product ID	2CSB204101R1400
EAN	8012542798101
Catalog Description	DDA204 A-40/0.03 Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, protection, against indirects contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.

Technical			
Standards		IEC/EN 61009 Ann. G	
Type of Residual Current		A type	
Rated Voltage (U <sub>r</sub> )		230/400 V	
Rated Operational Voltage		230/400 V	
Rated Insulation Voltage (U <sub>i</sub> )		500 V	
Rated Impulse Withstand Voltage (U <sub>imp</sub> )		4 kV	
Rated Current (I <sub>n</sub> )		40 A	
Rated Residual Current		30 mA	
0.0004.488	0004/04/00	0.11	

DDA204 A-40/0.03

Leakage Current Type	A
Rated Frequency (f)	50 60 Hz
Power Loss	4.8 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	4
Operating Characteristic	Instantaneous
Options Provided	
Connecting Capacity	Rigid 16 16 mm² Flexible 16 16 mm²
Environmental	
Ambient Temperature	-2555 °C
Ambient Air Temperature	Operation -2555 °C
Degree of Protection	IP2X
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 51505 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5614
REACH Declaration	9AKK108467A9482
Environmental Information	Refer to RoHS
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Technical UL/CSA	
Short-Circuit Current Rating (SCCR)	0.03 0.03 A
Dimensions	
Product Net Width	105 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.173 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross	3962 g
Weight	

Declaration of Conformity 9AKK106713A5614

## Installation

Instructions and Manuals 9AKK108467A7091

## Popular Downloads

Object Classification Code

Data Sheet, Technical 9AKK107991A8329 Information

Classifications		
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module	
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
CN8	85363030	
eClass	V11.0: 27142210	

## Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Modular DIN Rail Products} \rightarrow \text{Residual Current Devices RCD} \\ \text{Residual RCD} \\ \text{Residual Current Devices RCD} \\ \text{Residual RCD} \\ \text{Residual$ 





