

PRODUCT-DETAILS

QSD-DIG 230/24

QSD-DIG 230/24 Remote signalling panel



General Information

Extended Product Type	QSD-DIG 230/24
Product ID	2CSM273063R1521
EAN	8012542730637
Catalog Description	QSD-DIG 230/24 Remote signalling panel
Long Description	Remote signalling panel for visual and acoustic fault indication.

Technical

Rated Operational Voltage	500 ... 760 V AC
Rated Control Supply Voltage (U _s)	24 V DC
Model Number	AtRatedLoad 1 W Basic device
Delay Time (T)	Release 0...0 second [unit of time]
Mounting Orientation	Horizontal

Environmental

RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	9AKK106713A5709
Environmental	See RoHS Information

Information

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

Dimensions

Product Net Width	121 mm
Product Net Height	0.078 m
Product Net Depth / Length	55 mm
Product Net Weight	0.2 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.5 kg
Replacement Product ID (NEW)	2CSM257935R1521

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5709
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK107046A3897
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CSC004033B0202
-----------------------------------	-----------------

Classifications

ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90303100
eClass	V11.0 : 27371819

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Hospital Equipments (H+ Line) → Insulation Monitoring Devices for Medical Locations, ISOLTESTER - SELVTESTER - QSD

