

PRODUCT-DETAILS

ISL-C 600

ISL-C 600 Insulation Monitoring Device



General Information	
Extended Product Type	ISL-C 600
Product ID	2CSM656000R1500
EAN	8012542943006
Catalog Description	ISL-C 600 Insulation Monitoring Device
Long Description	ISL-C 6000 is an insulation monitoring device for ac circuits

Technical	
Rated Operational Voltage	60 760 V AC
Rated Control Supply Voltage (U _s)	(50 Hz) 100240 V (60 Hz) 100240 V
Model Number	Basic device
Delay Time (T)	Release 05 second [unit of time]
Options Provided	AC network

Environmental	
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	9AKK108467A8682
Environmental Information	See RoHS Information

ISL-C 600 2

Conflict Minerals 9AKK108468A3363
Reporting Template
(CMRT)

Dimensions	
Product Net Width	105 mm
Product Net Height	0.090 m
Product Net Depth / Length	44 mm
Product Net Weight	0.500 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.5 kg

Declaration of	9AKK108467A868
Conformity - CE	
onformity - CE	

Instructions and	No document needed
Manuals	

Popular Downloads	
Data Sheet, Technical	9AKK106930A8017
Information	

Classifications	
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90278099
eClass	V11.0 : 27371819

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Protection\ and\ Safety\ Devices\ \rightarrow\ Industrial\ Insulation\ Monitoring\ Devices$

ISL-C 600 3

