

PRODUCT-DETAILS

Sentry BSR23 Sentry BSR23 Safety relay



General Information	
Extended Product Type	Sentry BSR23
Product ID	2TLA010041R0600
EAN	7350024483277
Catalog Description	Sentry BSR23 Safety relay
Long Description	Sentry BSR23 Safety expansion relay with relay outputs 4NO+1NC, +24 VDC supply voltage and screw terminals. Used as expansion relay for a safety relay/safety PLC, in order to increase the number of safe outputs.
	Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility. Models with display offer preset configurations and extensive information to further simplify troubleshooting.
	Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s. High output current capacity of up to 6 A can save the use of an intermediary contactor. Multi-reset allows up to 10 safety relays connected to one reset light-button. All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories.

\cup	rc	lei	'n	ıg

EAN	7350024483277
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Sentry BSR23 2

Popular Downloads	
Data Sheet, Technical	2TLC010037L0201
Information	
Instructions and Manuals	2TLC010062M0201
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010006T0001
Marketing Video	2TLC010019N0201 2TLC010018N0201
D'accestina	
Dimensions	
Product Net Unight	22.5 mm
Product Net Height Product Net Depth /	
Length	120 11111
Product Net Weight	0.195 kg
Technical	
Function	Expansion relay - must be monitored by another device for higher than PL c
Sub-Function	Start/test input
Timer Relay Type	No Time Delay
Rated Control Supply Voltage (U_s)	24 V DC
Degree of Protection	IP20
Connecting Capacity	Crimped Pin 1x0.23.3 mm ² Crimped Pin 2x0.21.5 mm ²
	Flexible with Ferrule 1x0.23.3 mm ²
	Flexible with Ferrule 2x0.21.5 mm ² Solid 1x0.23.3 mm ²
	Solid 2x0.21.5 mm ²
Tightening Torque	0.7 N·m
Wire Stripping Length	6.5 mm
Recommended Screw Driver	M3.5
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	ISO 13849
Technical UL/CSA	
Connecting Capacity	Crimped Pin 1x 24-12 AWG
UL/CSA	Crimped Pin 2x 24-16 AWG Flexible with Ferrule 1x 24-12 AWG
	Flexible with Ferrule 2x 24-16 AWG
	Solid 1x 24-12 AWG Solid 2x 24-16 AWG
Environmental	
Ambient Air Temperature	Operation -25 +65 °C Storage -40 +70 °C
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU
Certificates and Declarations	
CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201

Sentry BSR23 3

cULus Certificate	2TLC010007D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
KC Certificate	2TLC010048D0201
TÜV Certificate	2TLC010008D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	31 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.256 kg
Package Level 1 EAN	7350024483277
Package Level 2 Units	36 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	9.5 kg

Object Classification Code	K
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
UNSPSC	39122331
E-Number (Finland)	2712521
E-Number (Sweden)	3860818

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{Control Products} \rightarrow \mbox{Electronic Relays and Controls} \rightarrow \mbox{Safety Relays} \rightarrow \mbox{Expansion Relays} \\ \mbox{Low Voltage Products and Systems} \rightarrow \mbox{Control Products} \rightarrow \mbox{Safety Products} \rightarrow \mbox{Safety Relays} \rightarrow \mbox{Expansion Relays} \\ \mbox{Expansion Relays} \rightarrow \m$

Sentry BSR23 4





