


# 465290240040

## Miniature Industrial relay 8 - 16 A



**Technical description:** Miniature Industrial relay, Spade/blade solder terminal, 2 pole, CO (nPDT), 8 A, AgNi, DC coil, 24 V, operating from 17.5 to 26.4 V, rated power 0.5 W, resistance 1200 Ω, consumption 20 mA, holding voltage 9.6 V, must drop-out voltage 2.4 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

**Commercial description:** Miniature industrial relay with 2 CO 8A contacts for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.

[BROWSE PRODUCT PAGE](#)

### Technical Features:

Ambient temperature range:	-40...70 °C
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	12.4x32.8x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage dc:	24 V
Operating range dc:	17.5...26.4 V
Rated current contact:	8 A
Rated power dc:	0.5 W
Rated voltage contact:	250 V AC
Supply version:	DC coil

Certifications and quality approvals (according to code):



**Need more information?**

[Contact our sales](#) [Find a dealer](#)