


466180120040

Miniature Industrial relay 8 - 16 A



Technical description: Miniature Industrial relay, Spade/blade terminal Faston, 1 pole, CO (nPDT), 16 A, AgNi, AC coil, 12 V, operating from 9.6 to 13.2 V, rated power 1.2 VA, resistance 80 Ω, consumption 90 mA, holding voltage 9.6 V, must drop-out voltage 2.4 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

Commercial description: Miniature industrial relay with 1 CO 16A contact for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	12.4x32.8x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage ac:	12 V
Operating range ac:	9.6...13.2 V
Rated current contact:	16 A
Rated power ac:	1.2 VA
Rated voltage contact:	250 V AC
Supply version:	AC coil

Certifications and quality approvals (according to code):



Need more information?

[Contact our sales](#) [Find a dealer](#)