


# 466190120040

## Miniature Industrial relay 8 - 16 A



**Technical description:** Miniature Industrial relay, Spade/blade terminal Faston, 1 pole, CO (nPDT), 16 A, AgNi, DC coil, 12 V, operating from 8.8 to 13.2 V, rated power 0.5 W, resistance 300 Ω, consumption 40 mA, holding voltage 4.8 V, must drop-out voltage 1.2 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

**Commercial description:** Miniature industrial relay with 1 CO 16A contact for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.

[BROWSE PRODUCT PAGE](#)

### Technical Features:

Ambient temperature range:	-40...70 °C
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	12.4x32.8x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage dc:	12 V
Operating range dc:	8.8...13.2 V
Rated current contact:	16 A
Rated power dc:	0.5 W
Rated voltage contact:	250 V AC
Supply version:	DC coil

Certifications and quality approvals (according to code):



**Need more information?**

[Contact our sales](#) [Find a dealer](#)