

601380120040

General purpose relay 6 - 10 A



Technical description: Industrial relay, 8 and 11 pin plug-in socket version, 3 pole, CO (nPDT), 10 A, AgNi, AC coil, 12 V, operating from 9.6 to 13.2 V, rated power 2.2 VA, resistance 19 Ω , consumption 183 mA, holding voltage 9.6 V, must drop-out voltage 2.4 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

Commercial description: General purpose industrial relay, 3 pole 10 A contacts, 11 pin plug-in. Equipped with lockable test button and mechanical indicator (preferred version). Available version with bifurcated contacts for low level switching: type 60.13-52xx, 3 pole, 6A, 11 pin plug-in.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Contact configuration:	3 pole, CO (nPDT)
Dimensions:	32.5x54.2x36.4 mm
Electrical life:	200000 cycles
Insulation coil/contacts:	3.6 kV
Nominal voltage ac:	12 V
Operating range ac:	9.6...13.2 V
Rated current contact:	10 A
Rated power ac:	2.2 VA
Rated voltage contact:	250 V AC
Supply version:	AC coil

Certifications and quality approvals (according to code):



RINA

Need more information?

[Contact our sales](#) [Find a dealer](#)