

601390240040

General purpose relay 6 - 10 A



Technical description: Industrial relay, 8 and 11 pin plug-in socket version, 3 pole, CO (nPDT), 10 A, AgNi, DC coil, 24 V, operating from 19.2 to 26.4 V, rated power 1.3 W, resistance 445 Ω , consumption 53.9 mA, holding voltage 12 V, must drop-out voltage 2.4 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

Commercial description: General purpose industrial relay, 3 pole 10 A contacts, 11 pin plug-in. Equipped with lockable test button and mechanical indicator (preferred version). Available version with bifurcated contacts for low level switching: type 60.13-52xx, 3 pole, 6A, 11 pin plug-in.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...70 °C
Contact configuration:	3 pole, CO (nPDT)
Dimensions:	32.5x54.2x36.4 mm
Electrical life:	200000 cycles
Insulation coil/contacts:	3.6 kV
Nominal voltage dc:	24 V
Operating range dc:	19.2...26.4 V
Rated current contact:	10 A
Rated power dc:	1.3 W
Rated voltage contact:	250 V AC
Supply version:	DC coil

Certifications and quality approvals (according to code):



Need more information?

[Contact our sales](#) [Find a dealer](#)