

# 601390480040

## General purpose relay 6 - 10 A



**Technical description:** Industrial relay, 8 and 11 pin plug-in socket version, 3 pole, CO (nPDT), 10 A, AgNi, DC coil, 48 V, operating from 38.4 to 52.8 V, rated power 1.3 W, resistance 1770 Ω, consumption 27.1 mA, holding voltage 24 V, must drop-out voltage 4.8 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

**Commercial description:** General purpose industrial relay, 3 pole 10 A contacts, 11 pin plug-in. Equipped with lockable test button and mechanical indicator (preferred version). Available version with bifurcated contacts for low level switching: type 60.13-52xx, 3 pole, 6A, 11 pin plug-in.

[BROWSE PRODUCT PAGE](#)

### Technical Features:

|                            |                   |
|----------------------------|-------------------|
| Ambient temperature range: | -40...70 °C       |
| Contact configuration:     | 3 pole, CO (nPDT) |
| Dimensions:                | 32.5x54.2x36.4 mm |
| Electrical life:           | 200000 cycles     |
| Insulation coil/contacts:  | 3.6 kV            |
| Nominal voltage dc:        | 48 V              |
| Operating range dc:        | 38.4...52.8 V     |
| Rated current contact:     | 10 A              |
| Rated power dc:            | 1.3 W             |
| Rated voltage contact:     | 250 V AC          |
| Supply version:            | DC coil           |

Certifications and quality approvals (according to code):



**Need more information?**

[Contact our sales](#) [Find a dealer](#)