



SIMATIC DP, electronic module for ET 200SP, F-DI 8x 24 V DC HF, 15 mm width, up to PLe (ISO 13849-1)/ SIL3 (IEC 61508)

Figure similar

General information	
Product type designation	F-DI 8x24VDC HF
Firmware version	
<ul style="list-style-type: none"> FW update possible 	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC01
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version STEP 7 configurable/integrated from version PROFINET from GSD version/GSD revision 	SIMATIC Safety V17 with HSP 0360 or higher as 6ES7136-6BA00-0CA0 GSDML V2.35
CIR - Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption, max.	40 mA; without load
Encoder supply	
Number of outputs	8
24 V encoder supply	
<ul style="list-style-type: none"> 24 V Short-circuit protection Output current per channel, max. Output current per module, max. 	Yes; min. L+ (-1.5 V) Yes; Electronic (response threshold 0.7 A to 1.8 A) 300 mA 800 mA; Total current of all encoders
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Inputs Outputs 	7 byte; S7-300/400F CPU, 6 byte 5 byte; S7-300/400F CPU, 4 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> Electronic coding element type F 	Yes
Digital inputs	

Number of digital inputs	8
Source/sink input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> for signal "0" 	-30 to +5 V
<ul style="list-style-type: none"> for signal "1" 	+15 to +30 V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	3.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes
— at "0" to "1", min.	0.4 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.4 ms
— at "1" to "0", max.	20 ms
for technological functions	
— parameterizable	No
Cable length	
<ul style="list-style-type: none"> shielded, max. 	1 000 m
<ul style="list-style-type: none"> unshielded, max. 	500 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
<ul style="list-style-type: none"> Hardware interrupt 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> RUN LED 	Yes; green LED
<ul style="list-style-type: none"> ERROR LED 	Yes; red LED
<ul style="list-style-type: none"> Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> Channel status display 	Yes; green LED
<ul style="list-style-type: none"> for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> for module diagnostics 	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> between the channels 	No
<ul style="list-style-type: none"> between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> between the channels and the power supply of the electronics 	No
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	Yes
Highest safety class achievable in safety mode	
<ul style="list-style-type: none"> Performance level according to ISO 13849-1 	PLe
<ul style="list-style-type: none"> Category according to ISO 13849-1 	Cat. 4
<ul style="list-style-type: none"> SIL acc. to IEC 61508 	SIL 3
Probability of failure (for service life of 20 years and repair time of 100 hours)	
— Low demand mode: PFDavg in accordance with SIL3	< 2.00E-05
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. 	0 °C
<ul style="list-style-type: none"> horizontal installation, max. 	60 °C
<ul style="list-style-type: none"> vertical installation, min. 	0 °C
<ul style="list-style-type: none"> vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	4 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual

Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	29 g

last modified: 8/7/2023 