



SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D, BU type A0, push-in terminals, without aux. terminals, new load group, WxH: 15x 117 mm

Figure similar

General information	
Product type designation	BU type A0
HW functional status	From FS06
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
<ul style="list-style-type: none"> <li>integrated</li> </ul>	Yes
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> <li>New potential group</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Potential group continued from the left</li> </ul>	No
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1; Type A0
Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
<ul style="list-style-type: none"> <li>for process terminals</li> </ul>	CC00 to CC09
<ul style="list-style-type: none"> <li>for AUX terminals</li> </ul>	does not exist
<ul style="list-style-type: none"> <li>for add-on terminals</li> </ul>	does not exist
connection method	
Terminals	
<ul style="list-style-type: none"> <li>Terminal type</li> </ul>	Push-in terminal
<ul style="list-style-type: none"> <li>system-integrated shield connection</li> </ul>	Yes; Optional

• Conductor cross-section, min.	0.14 mm <sup>2</sup> ; AWG 26
• Conductor cross-section, max.	2.5 mm <sup>2</sup> ; AWG 14
• Number of process terminals to I/O module	16
• Number of terminals to AUX bus	0
• Number of add-on terminals	0
• Number of terminals with connection to P1 and P2 bus	2

#### Dimensions

Width	15 mm
Height	117 mm
Depth	35 mm

#### Weights

Weight, approx.	40 g
-----------------	------

**last modified:** 8/7/2023 