

830102400000

Modular timer 8 - 12 - 16 A








Technical description: Modular timers, Multi-function, 1 CO (SPDT), 16 A, AC/DC coil, 240 V, operating from 16.8 to 265 V (AC)/(DC), rated power 1.5 VA (AC) / 2 W (DC), Version: Standard, ambient temperature from -20 to +60 °C

Commercial description: Modular timer, 22.5 mm wide, multi-voltage, multi-function, 1 contact, with the following functions: AI: On-Delay, DI: Interval, GI: Pulse delayed, SW: Symmetrical flasher (start pulse On), BE: Off-delay with control signal, CE: On and Off-Delay with control signal, DE: Interval with control signal on, WD: Watchdog

[BROWSE PRODUCT PAGE](#)

Technical Features:

Contact configuration:	1 CO (SPDT)
Delay setting:	(0.05...1)s, (0.5...10)s, (0.05...1)min, (0.5...10)min, (0.05...1)h, (0.5...10)h, (0.05...1)d, (0.5...10)d
Detail of functions:	Multi-function
Dimensions:	22.5x78.8x96 mm
Nominal voltage:	240 V
Operating range ac:	16.8...265 V
Operating range dc:	16.8...265 V
Rated current contact:	16 A
Rated voltage contact:	250 V AC
Certifications and quality approvals (according to code):	    

Need more information?

[Contact our sales](#) [Find a dealer](#)