



E5CC-RX3A5M-000

Termoregolatore, 1/16 DIN (48x48 mm), 1 uscita relè, 3 AUX, 100-240 V CA

| | |
|---------------------------------|--|
| Size | 1/16 DIN (48 x 48 mm) |
| Functions | ON/OFF control, PID control |
| Number of control loops | 1 |
| Temperature input type | B, C (WRe5-26), E, J, JPt100, K, L, N, P (PLII), Pt100, R, S, T, U |
| Linear analog input type | 0 to 10 V, 0 to 20 mA, 0 to 5 V, 1 to 5 V, 4 to 20 mA |
| Temperature range | -200-2300 °C |
| Number of event inputs | 0 |
| Number of alarm outputs | 3 |
| Supply voltage AC | 100-240 V |
| Control output | Relay |
| Terminal | Screw |

Libreria CAD




Digital Temperature Controllers Brochure

EN PDF 4,45 MB



E5CC Foglio istruzioni

EN PDF 223 KB



E5CC Guida "Pronti Via!"

EN PDF 5,23 MB



E5CC/E5EC Guida "Pronti Via!"

IT PDF 1,27 MB



E5CN-E5CC Conversion File Software

EN ZIP 613 KB



E5EC Foglio istruzioni

EN PDF 370 KB



E5_C Manuale sulla Comunicazione

EN PDF 7 MB



E5_C - Digital Temperature Controllers Manuale Utente

EN PDF 14,4 MB



E5_C/E5_C-T Digital Temperature Controller Catalogo tecnico

EN PDF 40,8 MB



EAC Mark removal Avviso di sospensione

EN PDF 221 KB



Panel Building Brochure

IT PDF 3,03 MB



Thermac Temperature Simulation Software

EN ZIP 16,2 MB



Thermac Temperature Simulation Tips and Tricks Guida "Pronti Via!"

EN PDF 381 KB