

# Product datasheet

Specifications



## Earth-leakage VigiPacT add-on protection module, ComPacT NSX 250, 200VAC to 440VAC, 30mA to 30A, 4 poles

LV429493

EAN Code: 3606481298591

### Main

Range Of Product	ComPacT NSX100...250 new generation ComPacT NSX100...250
Device Short Name	VigiPacT
Product Or Component Type	Vigi add-on
Device Application	Wiring
Range Compatibility	ComPacT new generation ComPacT NSX250 new generation circuit breaker ComPacT ComPacT NSX250 circuit breaker
Poles Description	4P
[In] Rated Current	250 A
Earth-Leakage Protection Class	Class A Class AC
Residual Earth-Leakage Sensitivity Adjustment Type	Adjustable
Earth-Leakage Sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
Residual Earth-Leakage Time Delay Adjustment Type	Adjustable
[Δt] Residual Earth-Leakage Time Delay Adjustment	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s 4 s

### Complementary

Network Type	AC
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-Leakage Protection	With
Maximum Breaking Time	800 ms
Overvoltage Category	IV

### Environment

---

Electrical Shock Protection Class	Class II
-----------------------------------	----------

---

Standards	IEC 60947-2
-----------	-------------

---

## Packing Units

---

Unit Type Of Package 1	PCE
------------------------	-----

---

Number Of Units In Package 1	1
------------------------------	---

---

Package 1 Height	13.5 cm
------------------	---------

---

Package 1 Width	14.2 cm
-----------------	---------

---

Package 1 Length	17.2 cm
------------------	---------

---

Package 1 Weight	1.34 kg
------------------	---------

---

Unit Type Of Package 2	S04
------------------------	-----

---

Number Of Units In Package 2	12
------------------------------	----

---

Package 2 Height	30.0 cm
------------------	---------

---

Package 2 Width	40.0 cm
-----------------	---------

---

Package 2 Length	60.0 cm
------------------	---------

---

Package 2 Weight	16.52 kg
------------------	----------

---

Unit Type Of Package 3	P12
------------------------	-----

---

Number Of Units In Package 3	48
------------------------------	----

---

Package 3 Height	42.0 cm
------------------	---------

---

Package 3 Width	80.0 cm
-----------------	---------

---

Package 3 Length	120.0 cm
------------------	----------

---

Package 3 Weight	78.0 kg
------------------	---------

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)