

QUINT-PS/24DC/48DC/ 5 - DC/DC converter



2320128

<https://www.phoenixcontact.com/gb/products/2320128>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Primary-switched QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 48 V DC/5 A

Product description

QUINT DC/DC converter with maximum functionality

DC/DC converters alter the voltage level, regenerate the voltage at the end of long cables or enable the creation of independent supply systems by means of electrical isolation.

QUINT DC/DC converters magnetically and therefore quickly trip circuit breakers with six times the nominal current, for selective and therefore cost-effective system protection. The high level of system availability is additionally ensured, thanks to preventive function monitoring, as it reports critical operating states before errors occur.

Your advantages

- Reliable starting of difficult loads, thanks to the static POWER BOOST power reserve with up to 125% nominal current permanently
- Preventive function monitoring indicates critical operating states before errors occur
- Constant voltage: output voltage regenerated even at the end of long cables
- Support conversion to various voltage levels
- Electrical isolation: for setting up independent supply systems

Technical data

Input data

DC operation

| | |
|---|---|
| Nominal input voltage range | 24 V DC |
| Input voltage range | 18 V DC ... 32 V DC |
| Extended input voltage range in operation | 14 V DC ... 18 V DC (Derating) |
| Wide-range input | no |
| Input voltage range DC | 18 V DC ... 32 V DC 14 V DC ... 18 V DC (Consider derating during operation) |
| Voltage type of supply voltage | DC |
| Inrush current | < 15 A (typical) |
| Inrush current integral (I^2t) | 3 A ² s |
| Mains buffering time | > 12 ms (24 V DC) |
| Current consumption | 14 A (24 V, I _{BOOST}) |
| Reverse polarity protection | ≤ yes 30 V DC |
| Protective circuit | Transient surge protection; Varistor |
| Input fuse | 25 A (internal (device protection)) |

Output data

| | |
|---|--|
| Efficiency | > 92.5 % |
| Output characteristic | U/I |
| Nominal output voltage | 48 V DC ±1 % |
| Setting range of the output voltage (U _{Set}) | 30 V DC ... 56 V DC (> 48 V DC, constant capacity restricted) |
| Nominal output current (I _N) | 5 A (-25 °C ... 60 °C) |
| POWER BOOST (I _{Boost}) | 6.25 A (-25 °C ... 40 °C permanent, U _{OUT} = 48 V DC) |
| Selective Fuse Breaking (I _{SFB}) | 30 A (12 ms) |
| Magnetic circuit breaker tripping | B2 / B4 / C2 |
| Derating | 60 °C ... 70 °C (2.5 %/K) |
| Feedback voltage resistance | 60 V DC |
| Protection against overvoltage at the output (OVP) | < 60 V DC |
| Max. capacitive load | unlimited |
| Active current limitation | Approximately 7 A |
| Control deviation | < 1 % (change in load, static 10 % ... 90 %) < 2 % (change in load, dynamic 10 % ... 90 %) < 0.1 % (change in input voltage ±10 %) |
| Residual ripple | < 20 mV _{PP} |
| Output power | 240 W |
| Peak switching voltages nominal load | < 10 mV _{PP} (20 MHz) |
| Maximum no-load power dissipation | 5.2 W |
| Power loss nominal load max. | 21 W |
| Rise time | < 2 ms (U _{OUT} (10 % ... 90 %)) |
| Connection in parallel | yes, for redundancy and increased capacity |

QUINT-PS/24DC/48DC/ 5 - DC/DC converter



2320128

<https://www.phoenixcontact.com/gb/products/2320128>

| | |
|----------------------|-----|
| Connection in series | yes |
|----------------------|-----|

Signal: DC OK active

| | |
|-------------------------|--|
| Output description | $U_{OUT} > 0.9 \times U_N$: High signal |
| Switching voltage range | 24 V DC |
| Maximum inrush current | < 20 mA (short-circuit-proof) |

Signal: POWER BOOST, active

| | |
|-------------------------|-------------------------------|
| Output description | $I_{OUT} < I_N$: High signal |
| Switching voltage range | 24 V DC |
| Maximum inrush current | < 20 mA (short-circuit-proof) |

Signal: U_{IN} OK, active

| | |
|-------------------------|------------------------------------|
| Output description | $U_{IN} > 19.2$ V: High signal |
| Switching voltage range | 24 V DC |
| Maximum inrush current | ≤ 20 mA (short-circuit-proof) |

Signal: DC OK floating

| | |
|------------------------|-------------------|
| Output description | Relay |
| Output voltage | ≤ 30 V AC/DC |
| Maximum inrush current | ≤ 100 mA |

Connection data

Input

| | |
|---------------------------------------|----------------------------|
| Connection method | Pluggable screw connection |
| Conductor cross section, rigid min. | 0.2 mm ² |
| Conductor cross section, rigid max. | 2.5 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Stripping length | 8 mm |
| Screw thread | M3 |
| Tightening torque, min | 0.5 Nm |
| Tightening torque max | 0.6 Nm |

Output

| | |
|---------------------------------------|----------------------------|
| Connection method | Pluggable screw connection |
| Conductor cross section, rigid min. | 0.2 mm ² |
| Conductor cross section, rigid max. | 2.5 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Stripping length | 7 mm |
| Screw thread | M3 |

QUINT-PS/24DC/48DC/ 5 - DC/DC converter



2320128

<https://www.phoenixcontact.com/gb/products/2320128>

| | |
|------------------------|--------|
| Tightening torque, min | 0.5 Nm |
| Tightening torque max | 0.6 Nm |

Signal

| | |
|---------------------------------------|---------------------|
| Conductor cross section, rigid min. | 0.2 mm ² |
| Conductor cross section, rigid max. | 2.5 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Screw thread | M3 |
| Tightening torque, min | 0.5 Nm |
| Tightening torque max | 0.6 Nm |

Signaling

| | |
|--------------------|-------------------------|
| Types of signaling | LED |
| | Active switching output |
| | Relay contact |

Signal output: DC OK active

| | |
|----------------|-------------------|
| Status display | "DC OK" LED green |
| Color | green |

Signal output: POWER BOOST, active

| | |
|------------------------|--|
| Status display | "BOOST" LED yellow/ $I_{OUT} > I_N$: LED on |
| Color | yellow |
| Note on status display | LED on |

Signal output: U_{IN} OK, active

| | |
|------------------------|---|
| Status display | LED " $U_{IN} < 19.2$ V" yellow/ $U_{IN} < 19.2$ V DC: LED on |
| Color | yellow |
| Note on status display | LED on |

Signal output: DC OK floating

| | |
|------------------------|---|
| Note on status display | $U_{OUT} > 0.9 \times U_N$: Contact closed |
|------------------------|---|

Electrical properties

| | |
|---------------------------------|---------------------|
| Number of phases | 1.00 |
| Insulation voltage input/output | 1.5 kV (type test) |
| | 1 kV (routine test) |
| | 1 kV (type test) |

Product properties

| | |
|----------------------------|--------------------|
| Product type | DC/DC converters |
| MTBF (IEC 61709, SN 29500) | > 761000 h (40 °C) |

Insulation characteristics

| | |
|---------------------|-----|
| Protection class | III |
| Degree of pollution | 2 |

Dimensions

| | |
|--------|--------|
| Width | 48 mm |
| Height | 130 mm |
| Depth | 125 mm |

Installation dimensions

| | |
|---|---------------------------------------|
| Installation distance right/left | 0 mm / 0 mm ($\leq 70\text{ °C}$) |
| Installation distance right/left (active) | 15 mm / 15 mm ($\leq 70\text{ °C}$) |
| Installation distance top/bottom | 50 mm / 50 mm ($\leq 70\text{ °C}$) |
| Installation distance top/bottom (active) | 50 mm / 50 mm ($\leq 70\text{ °C}$) |

Alternative assembly

| | |
|--------|--------|
| Width | 122 mm |
| Height | 130 mm |
| Depth | 51 mm |

Mounting

| | |
|-------------------------|---|
| Mounting type | DIN rail mounting |
| Assembly instructions | alignable: $P_N \geq 50\%$, 5 mm horizontally, 15 mm next to active components, 50 mm vertically alignable: $P_N < 50\%$, 0 mm horizontally, 40 mm vertically top, 20 mm vertically bottom |
| Mounting position | horizontal DIN rail NS 35, EN 60715 |
| With protective coating | No |

Material specifications

| | |
|------------------|---|
| Housing material | Metal |
| Type of housing | Aluminum (AlMg3) |
| Hood version | Galvanized sheet steel, free from chrome (VI) |

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -25 °C ... 70 °C (> 60 °C derating, 2.5 %/K, startup at -40°C type-tested) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Ambient temperature (start-up type tested) | -40 °C |
| Climatic class | 3K3 (in acc. with EN 60721) |
| Max. permissible relative humidity (operation) | $\leq 95\%$ (at 25 °C, non-condensing) |
| Shock | 18 ms, 30g, in each space direction (according to IEC 60068-2-27) |
| Vibration (operation) | < 15 Hz, amplitude ± 2.5 mm (according to IEC 60068-2-6) 15 Hz ... 150 Hz, 2.3g, 90 min. |

Standards and regulations

| | |
|--|----------------------------|
| Rail applications | EN 50121-4 |
| Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations | EN 50178/VDE 0160 (PELV) |
| Standard - Electrical safety | EN 60950-1/VDE 0805 (SELV) |
| Standard – Safety extra-low voltage | EN 60950-1 (SELV) |
| | EN 60204 (PELV) |
| Standard - Safe isolation | DIN VDE 0100-410 |

Approvals

| | |
|-----------------------|--|
| Shipbuilding approval | DNV GL (EMC B) |
| UL approvals | UL/C-UL listed UL 508 |
| | UL/C-UL Recognized UL 60950-1 |
| | UL ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D (Hazardous Location) |

EMC data

| | |
|-------------------------------------|---|
| EMC requirements for noise emission | EN 61000-6-3 |
| | EN 61000-6-4 |
| EMC requirements for noise immunity | EN 61000-6-1 |
| | EN 61000-6-2 |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |

Electrostatic discharge

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

Electrostatic discharge

| | |
|-------------------|----------------------|
| Contact discharge | 8 kV (Test Level 4) |
| Discharge in air | 15 kV (Test Level 4) |
| Comments | Criterion A |

Electromagnetic HF field

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-3 |
|-----------------------|--------------|

Electromagnetic HF field

| | |
|---------------------|-------------------|
| Frequency range | 80 MHz ... 1 GHz |
| Test field strength | 10 V/m |
| Frequency range | 1.4 GHz ... 2 GHz |
| Test field strength | 10 V/m |
| Frequency range | 2 GHz ... 3 GHz |
| Test field strength | 10 V/m |
| Comments | Criterion A |

Fast transients (burst)

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-4 |
|-----------------------|--------------|

Fast transients (burst)

QUINT-PS/24DC/48DC/ 5 - DC/DC converter



2320128

<https://www.phoenixcontact.com/gb/products/2320128>

| | |
|----------|------------------------------------|
| Input | 2 kV (Test Level 3 - asymmetrical) |
| Output | 2 kV (Test Level 3 - asymmetrical) |
| Signal | 2 kV (Test Level 4 - asymmetrical) |
| Comments | Criterion A |

Surge voltage load (surge)

| | |
|-----------------------|---|
| Standards/regulations | EN 61000-4-5 |
| Input | 1 kV (Test Level 2 - symmetrical) 2 kV (Test Level 3 - asymmetrical) |
| Output | 1 kV (Test Level 2 - symmetrical) 2 kV (Test Level 3 - asymmetrical) |
| Signal | 1 kV (Test Level 2 - asymmetrical) |
| Comments | Criterion A |

Conducted interference

| | |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-6 |
|-----------------------|--------------|

Conducted interference

| | |
|-----------------|---------------------|
| I/O/S | asymmetrical |
| Frequency range | 0.15 MHz ... 80 MHz |
| Comments | Criterion A |
| Voltage | 10 V (Test Level 3) |

Emitted interference

| | |
|--|--|
| Standards/regulations | EN 61000-6-3 |
| Radio interference voltage in acc. with EN 55011 | EN 55011 (EN 55022) Class B, area of application: Industry and residential |
| Emitted radio interference in acc. with EN 55011 | EN 55011 (EN 55022) Class B, area of application: Industry and residential |

Criteria

| | |
|-------------|--|
| Criterion A | Normal operating behavior within the specified limits. |
| Criterion B | Temporary impairment to operational behavior that is corrected by the device itself. |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk