


Linear power supply IN:
12-24Vac / OUT: 1.2...24Vdc 0.8...5A

| | |
|--|--|
| Series | with adjustable output |
| Code | XCL5R |
| Type | CL5R |
| HS code | 85044083 |
| INPUT TECHNICAL DATA | |
| Input rated voltage | 12-24 Vac |
| Input voltage AC | 10...26 Vac (see Tab. 1) |
| Frequency | 47...63 Hz |
| Current consumption | 6 A (24 Vac) |
| Internal protection fuse | T 10 A |
| External protection on AC line | MT: C-10 A / Fuse: T 10 A |
| OUTPUT TECHNICAL DATA | |
| Output voltage range | 1.2...24 Vdc |
| Output adjustable range | (see Table 1 and Table 2) |
| Continuous current | 0.8...5 A (see Tab. 2) |
| Ripple @ nominal ratings | < 50 mVpp a 24 Vac |
| Hold up time | >20 ms |
| Status indication | LED "DC OK" |
| GENERAL TECHNICAL DATA | |
| Operating temperature range | -20...+45°C |
| Input / output isolation | not insulated |
| Input / ground isolation | 0.5 kVac / 60 s |
| Output / ground isolation | 0.5 kVac / 60 s |
| Alarm contact | |
| Parallel connection | |
| Overvoltage category / pollution degree | II / 2 |
| Protection degree | IP 00 |
| Connection terminal | 2.5 mm ² / 2.5 mm ² |
| Housing material | aluminium |
| Dimensions (LxHxD) | 37x115x118 mm |
| Approximate weight | 350 g |
| Mounting information | vertical on a rail, 20 mm from adjacent components |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| APPROVALS AND MARKINGS | CE, |



DESCRIZIONE DEL PRODOTTO

Linear power supply IN: 12-24 Vac / OUT: 1.2...24 Vdc 0.8...5 A